

NEW

PiLoTREK WP-200

INTEGRATED 80 GHz (W-BAND) RADAR
FOR LIQUIDS & SOLIDS

80
GHz



5 YEARS WARRANTY

NIVELCO

LEVEL TRANSMITTERS

FEATURES

- 2-wire 80 GHz (W-band) radar
- Accuracy of ± 2 mm (0.078")
- Easy to install due to small antenna diameter
- 1", 1½" encapsulated horn antenna
- Submersible – integrated design with IP66/IP68 (NEMA 4X/6P) protection
- User-friendly threshold management
- Configuration via Bluetooth® with MobileEView app
- PACTware™ compatible
- 5 years warranty
- Ex variant

APPLICATIONS

- For measuring the level of liquids, emulsions, and other media
- For free flowing solids
- Storage tanks, chemical tanks, open pits, sumps, wells
- Measurement through a plastic tank roof
- For material prone to vapor formation
- For measuring liquids with a gas blanket
- It can also be used in a vacuum
- Open-channel flow measurement

The new **PiloTREK WP-200** non-contact radar level transmitters use the most advanced industrial measurement technology, the 80 GHz FMCW radar. The most fundamental advantage of 80 GHz radars compared to lower frequencies (5...12 GHz and 25 GHz) is the smaller antenna size, better focusability, and narrow beam angle.

It uses the latest technology for measuring liquids, masses, emulsions, and other chemicals widely used in, for example, the water industry, food industry, energy industry, pharmaceutical industry, and chemical industry, which provides measurement results with millimeter accuracy. It is also excellent for measuring substances prone to vapor formation and liquids with gas blanket or large-particle bulk solids. In addition to the level, volume, and weight measurement functions, this product family also inherits the open-channel flow measurement functions and the threshold functions to eliminate false and interfering echoes. Since no medium is required for millimeter waves to propagate, it can also be used in a vacuum. The device can also be operated with HART® compliant **NIVELCO EView2**, **MultiCONT** universal process controller, and **PACTware™** software, or programmed via Bluetooth® communication with the new **MobileEView** app.

CERTIFICATES

- ATEX (*Ex ia GD*)
- IECEx (*Ex ia GD*)
- INMETRO (*Ex ia GD*),
- ANATEL

AREAS OF APPLICATION

- Water and wastewater industry
- Energy industry / Plant utilities
- Food & Beverage
- Pharmaceutical industry
- Chemical industry
- Marine applications
- Agriculture
- Construction materials
- Heavy industry
- Packaging industry




WP□-2□4-4



WP□-2□2-4

LINEARITY ERROR



OPERATING PRINCIPLE

The reflection of the millimeter-waves is highly dependent on the dielectric constant of the medium. Therefore, the measured medium's dielectric constant (ϵ_r) must be over 1.9 for millimeter-wave level measurement. The measurement principle of a level transmitter with a millimeter-waves signal is based on measuring the reflection's time of flight.

Informative ϵ_r values							
Butane (C ₄ H ₁₀)	1.4	Ethers	4.4	Gasoline	2.3	Methyl alcohol (CH ₃ OH)	33.1
LP gas	1.6...1.9	Acetic acid (CH ₃ COOH)	6.2	Bitumen	2.6	Glycol (C ₂ H ₆ O ₂)	37
Kerosene	2.1	Limestone	6.1...9.1	Carbon disulfide (CS ₂)		Nitrobenzene (C ₆ H ₅ NO ₂)	40
Crude Oil		Ammonia (NH ₃)	17...26	Clinker	2.7	Glycerin (C ₃ H ₈ O ₃)	41.1
Diesel Oil	2.2	Acetone (C ₃ H ₆ O)	21	Resin	2.4...3.6	Water (H ₂ O)	80
Benzol (C ₆ H ₆)		Ethyl alcohol (C ₂ H ₅ OH)	24	Cereal Grain	3...5	Sulphuric acid (H ₂ SO ₄) (T = 20 °C [68 °F])	84

The speed of propagation of millimeter-waves signals in the air, gases, and vacuum is almost constant regardless of temperature and medium pressure, so the measured distance does not depend on the physical parameters of the intermediate medium. The **PiloTREK WP-200** level transmitter is a continuous-wave frequency modulated radar (FMCW) operating at 80 GHz (W-band). The most obvious advantages of 80 GHz radars over lower frequency (5...12 & 25 GHz) radars are smaller antenna size, better focus, and smaller beam angle. A portion of the millimeter-wave continuous wave energy radiated by the level transmitter antenna is reflected from the measured surface, depending on the material to be measured. The distance of the reflecting surface is calculated with high accuracy by the electronics from the frequency shift of the reflected signal and converted into a distance, level, or volume signal by the electronics.

TECHNICAL DATA

		PVDF housing WPB, WPT-2□□-□	PP housing WPA-2□□-□
Measured values		Distance; Calculated values: level, volume, mass, flow	
Signal frequency		77...81 GHz (W-band)	
Measuring range ⁽¹⁾		0...30 m (0...98.5 ft)	
Lowest ε _r of medium		1.9	
Resolution		0.1 mm (0.04")	
Supply voltage		12...36 V DC	
Output	Analog	4...20 mA (3.9...20.5 mA); R _{Lmax} = (U _S – 12 V) / 0.02 A	
	Digital	Bluetooth® LE 5.1 (optional), HART® interface (loop resistance ≥250 Ω)	
	Service interface	SAT-504-3 compatible; galvanically isolated; 3.3 V LVDS; max. 100 mA	
	Relay (optional)	SPDT 30 V / 1 A DC; 42 V / 0.5 A AC	
Measuring frequency		~1/s	
Antenna material ⁽¹⁾		Encapsulated horn antenna (PP / PVDF / PTFE)	
Process temperature		-40...+80 °C (-40...+176 °F)	-30...+80 °C (-22...+176 °F)
Ambient temperature			
Process pressure		-1...3 bar (-14.5...43.5 psi)	
Process connection		1", 1½" BSP / NPT	
Ingress protection		IP66 / IP68 (NEMA 4X / 6P)	
Electrical connection		4× 0.5 mm ² shielded Ø6 mm cable × 5 m (up to 30 m); For relay option: 7× 0.5 mm ² shielded cable [4× AWG22 shielded cable × 16.4 ft (up to 98.5 ft); For relay option: 7× AWG22 shielded cable]	
Electrical protection		Overvoltage Class 1; (Class III [SELV])	
Housing material ⁽¹⁾		Plastic (PP / PVDF)	
Weight		~ 600 g (~ 1.32 lb)	

⁽¹⁾ Depending on order code.

TYPE-DEPENDENT DATA

	WP□-212-□ WP□-213-□	WP□-214-□ WP□-215-□	WP□-224-□ WP□-225-□
Dead zone ⁽²⁾	0 m		
Maximum measuring range ⁽³⁾	10 m (33 ft)		20 m (66 ft)
Accuracy ⁽⁴⁾	±4 mm (±0.157")		±2 mm (0.078")
Beam angle (-3 dB)	12°	7°	
Antenna insertion length ⁽⁵⁾	56 mm (2.2")	70 mm (2.75")	
Lower process connection	1" BSP / NPT	1½" BSP / NPT	
Upper process connection	1" BSP		

⁽²⁾ Measured from the tip of the antenna.

⁽³⁾ In the case of an ideal reflecting surface.

⁽³⁾ May be limited in the case of low dielectric constant or non-perpendicular or non-planar media.

⁽⁵⁾ Measured from the sealing plane of the process connection.

Ex INFORMATION

	WP□-2□□-8 Ex, WP□-2□□-E Ex	
ATEX certificate number	BK124ATEX001 X	
Ex marking (ATEX)	Ⓔ II 1 G Ex ia IIC T5 Ga	Ⓔ II 1 D Ex ia IIIC T95°C Da
INMETRO certificate number	DNV 24.0166 X	
Ex marking (INMETRO)	Ex ia IIC T5 Ga	Ex ia IIIC T95°C Da
Ex power supply, intrinsically safety data ⁽⁶⁾	$U_i = 30 \text{ V}, I_i = 100 \text{ mA}, P_i = 0.75 \text{ W}$	$U_i = 30 \text{ V}, I_i = 140 \text{ mA}, P_i = 1 \text{ W}$
	$C_i \leq 12 \text{ nF} + 0.12 \text{ nF/m cable}, L_i \leq 238 \text{ µH} + 0.65 \text{ µH/m cable}$ with standard 5 m cable: $C_i \leq 12.5 \text{ nF}, L_i \leq 242 \text{ µH}$	
Supply voltage	12...30 V DC	

⁽⁶⁾ In IIB applications, Ex power supply data for IIIC can be used.

TEMPERATURE DATA FOR Ex CERTIFIED MODELS

	WP□-2□□-8 Ex, WP□-2□□-E Ex	
	Hazardous gas atmospheres	Explosive dust atmospheres
Temperature data	Ex ia IIC	Ex ia IIIC
Temperature class	T5	T95°C
Highest ambient temperature	+80 °C (+176 °F)	
Highest surface temperature of the instrument ⁽⁷⁾		

⁽⁷⁾ Conducted or radiated heat transferred by medium, ambient or process connection.


POLARIZATION

The **PiloTREK W-200** 80 GHz radar is much less sensitive to installation conditions, both in terms of polarization and clutter sensitivity, due to its narrow and nearly circular beamwidth.

BACKGROUND MAPPING

Thanks to its 80 GHz FMCW technology, it is much less sensitive to the presence of clutter than previous generation radars. It now has an easy-to-use, flexible threshold management (EView2) that allows echoes from clutter in the tank to be easily masked if necessary. The threshold curve is designed to mask unwanted echoes from the measurement. Echo peaks below the threshold are not included in the evaluation.

WIRING



The **BROWN (+)** / **WHITE (-)** wires are the 4...20 mA output or power supply. The **GREY**, **BLUE** and **PINK** wires are for relay output and are only available in relay version. The **YELLOW** and **GREEN** wires are for servicing purposes only and are hidden by default. The **BLACK** is the cable shielding.


MOUNTING

The device must be mounted far as possible from interfering objects inside the tank and sources of interference, such as waves, vortex or strong vibrations. The antenna cover must be parallel to the measured surface within $\pm 2...3^\circ$. In regions with extremely hot climates, we recommend protecting the instrument from direct sunlight to avoid exceeding the ambient temperature limits of the housing.




Bluetooth® CONNECTIVITY

The Bluetooth® option on the **PiloTREK W-200 Series** allows for convenient device setup and diagnostics via the NIVELCO **MobileEView** app for Android or iOS or the free **EView2** software download for laptops.




PiLoTREK TRANSMITTERS IN HART® MULTIDROP LOOP


MultiCONT multi-channel remote controllers process, display, and transmit data from NIVELCO's HART®-equipped transmitters in a multidrop loop. Up to 15 of these connected transmitters can be programmed and maintained from MultiCONT, which supports data-logging tasks. MultiCONT provides programmable relay outputs, while 4...20 mA outputs are available through remote I/O modules.




MultiCONT can send measurement data via RS485 to PLCs, computers running third-party SCADA systems, or the NIVELCO NIVISION inventory monitoring system.




APPLICATIONS




APPLICATIONS



DIMENSIONS



WP□-212-□, WP□-213-□



WP□-2□4-□, WP□-2□5-□

ORDER CODES

(NOT ALL COMBINATIONS AVAILABLE)

Advanced 80 GHz radar level transmitters

PiloTREK WP□ - 2□□ - □⁽¹⁾

Integrated type	Antenna / Housing material	Code	80 GHz	Measurement distance	Code	Process connection - lower / upper	Code	Output / Ex	Code
	PP / PP	A		10 m (33 ft)	1	1" BSP / 1" BSP ⁽³⁾	2	-	4
	PVDF / PVDF	B		20 m (66 ft)	2	1" NPT / 1" BSP ⁽³⁾	3	Ex ia	8
	PTFE / PVDF	T		30 m (98.5 ft) ⁽²⁾	3	1 1/2" BSP / 1" BSP ⁽⁴⁾	4	+ Relay	H
						1 1/2" NPT / 1" BSP ⁽⁴⁾	5	+ Bluetooth®	B
						2" BSP / 1" BSP ^(2, 5)	6	Bluetooth® / Ex ia GD	E
						2" NPT / 1" BSP ^(2, 5)	7	+ Relay	R
						Ø75 mm (2 1/2") / 1" BSP ^(2, 6)	8	+ Bluetooth®	R



Use the NIVELCO Selector to configure your PiloTREK to best suit your application.

⁽¹⁾ For explosion-proof devices, the article number is followed by "Ex" on the data plate.

⁽²⁾ Under development.

⁽³⁾ Only for 10 m (33 ft) measuring range.

⁽⁴⁾ Only for 10 m (33 ft) or 20 m (66 ft) measuring range.

⁽⁵⁾ Only for 20 m (66 ft) measuring range.

⁽⁶⁾ Only for 30 m (98.5 ft) measuring range.

The project 2020-1.1.2-PIACI-KFI-2021-00278 was funded by the Ministry of Culture and Innovation through the National Research Development and Innovation Fund, under the Market-driven Research, Development and Innovation Projects (2020-1.1.2-PIACI-KFI) call for proposals.

